

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1-6. (Canceled)

7. (Currently Amended) Mobile equipment comprising:

a single pickup device picking up an image of a subject;

a parallax information portion determining parallax information of said subject based on
a distance between human eyes;

a three dimensional image creation portion creating a three dimensional image by applying said parallax information to said image; and

a display unit displaying said three dimensional image,

wherein said three dimensional image creation portion cuts a human face out of said image picked up, to obtain a face image and provides said face image with said parallax information.

8. (Original) The mobile equipment of claim 7, wherein said pickup device is a pickup device for picking up a two dimensional image.

9. (Original) The mobile equipment of claim 8, further comprising:

a communication control portion controlling a communication with another device; and
a transmission and reception portion allowing a call to and from another device.

10. (Currently Amended) Mobile equipment comprising:

a single pickup device picking up an image of a subject;

a parallax information portion determining parallax information of said subject based on
a distance between human eyes;

a three dimensional image creation portion creating a three dimensional image by
applying said parallax information to said image; and

a display unit displaying said three dimensional image,

wherein said three dimensional image creation portion selects a particular subject from
said image picked up, to obtain an image of the subject and provides said image of the subject
and an image included in said image picked up other than said particular subject with different
parallax information, respectively.

11. (Original) The mobile equipment of claim 10, wherein said pickup device is a
pickup device for picking up a two dimensional image.

12. (Original) The mobile equipment of claim 11, further comprising:

a communication control portion controlling a communication with another device; and

a transmission and reception portion allowing a call to and from another device.

13. (Currently Amended) A three dimensional conversion program product causing a computer to execute a three dimensional conversion process comprising the steps of:

inputting a two dimensional image;

cutting a human face image out of said two dimensional image to obtain a face image;

determining parallax information of said face image based on a distance between human eyes;

creating a three dimensional image by applying said parallax information to said face image; and

outputting said three dimensional image.

14. (Canceled)

15. (Previously Presented) Mobile equipment comprising:

a pickup device picking up an image of a subject;

a parallax information portion determining parallax information of said subject;

a three dimensional image creation portion creating a three dimensional image by applying said parallax information to said image; and

a display unit displaying said three dimensional image,

wherein said parallax information portion calculates said parallax information based on the brightness of the image.

16. (Previously Presented) Mobile equipment comprising:

- a pickup device picking up an image of a subject;
- a parallax information portion determining parallax information of said subject;
- a three dimensional image creation portion creating a three dimensional image by applying said parallax information to said image; and
- a display unit displaying said three dimensional image,

wherein said parallax information portion calculates said parallax information based on the intensity of light reflected from the subject.

17. (Previously Presented) Mobile equipment comprising:

- a pickup device picking up a two dimensional image data of a subject;
- a three dimensional image creation portion obtaining display data for three dimensional display, the display data including image data for a right eye and for a left eye, wherein said three dimensional image creation portion includes,

- a first data process means for generating three dimensional data derived from the two dimensional data; and
- a second data process means for converting the three dimensional data into the image data for the right eye and the image data for the left eye; and

a display unit displaying an image for the three dimensional display based on the display data.

18. (Previously Presented) The mobile equipment of claim 17, wherein said display unit includes a switching liquid crystal element switchable in deflection angle, and a patterned phase difference plate patterned in a slit;

said mobile equipment further comprising a controlling portion to change a relationship of said liquid crystal element phase and said phase difference plate.

19. (Previously Presented) The mobile equipment of claim 18, wherein said display unit further includes a liquid crystal including a plurality of pixels and said controlling portion changes the relationship to prevent an image for the three dimensional display from passing through the pixels.

20. (Previously Presented) The mobile equipment of claim 18, further comprising operation keys receiving an input, wherein said controlling portion changes the relationship based on the input.

21. (Previously Presented) The mobile equipment of claim 17, wherein said pickup device is a single pickup device.

22. (Previously Presented) The mobile equipment of claim 17, further comprising
a communication control portion controlling a communication with another device; and
a transmission and reception portion allowing a call to and from another device.

23. (Previously Presented) The mobile equipment of claim 17, further comprising
a memory for storing a face geometry model, wherein said three dimensional image
creation portion further includes an extraction means for extracting a human face image data out
of the two dimensional image data, wherein said first data process means generates the three
dimensional data from the human face image data based on the face geometry model.

24. (Previously Presented) The mobile equipment of claim 17, further comprising a
three dimensional shutter button to pick up the two dimensional image data, wherein said three
dimensional image creation portion obtains the display data in response to press of said three
dimensional shutter button.

25. (Previously Presented) The mobile equipment of claim 17, further comprising
a dividing portion for dividing the two dimensional image data picked up by said pickup
device into a plurality of blocks; and
a detecting portion for detecting the brightness of each of said plurality of blocks,
wherein

said three dimensional image creation portion generates the display data in response to the brightness of each of said plurality of blocks.

26. (Previously Presented) The mobile equipment of claim 17, further comprising
a radiation unit illuminating the subject with light; and
a detection portion detecting the intensity of the light,
wherein said three dimensional image creation portion obtains the display data in response to the intensity of the light.

27. (Previously Presented) The mobile equipment of claim 17, further comprising
operation keys for receiving an input for selection of a subject from the background in the two dimensional image displayed on said display unit, wherein
said three dimensional image creation portion further includes a selection data process means for generating the two dimensional image data of the subject in response to the selection.

28. (Previously Presented) The mobile equipment of claim 27, wherein said operation keys receive inputs for the selection of a plurality of subjects and said selection data process means generates the two dimensional image data for each of the selected subjects.

29. (Previously Presented) A three dimensional conversion program product causing a computer to execute a three dimensional conversion process comprising the steps of:

receiving an input of a two dimensional image data of a subject;

obtaining display data for three dimensional display, the display data including image data for a right eye and for a left eye, wherein said step of obtaining the display data includes the steps of:

generating three dimensional data derived from the two dimensional data; and

converting the three dimensional data into the image data for the right eye and the image data for the left eye; and the process further comprising
outputting the display data.

30. (New) The mobile equipment of claim 15, wherein said parallax information of said subject is determined based on a distance between human eyes.

31. (New) The mobile equipment of claim 16, wherein said parallax information of said subject is determined based on a distance between human eyes.